



# Material Safety Data Sheet

Date of printing : 3/28/2008.

Date of issue : 3/28/2008.

## 1 . Product and company identification

Prepared For

Prepared by

Akzo Nobel Coatings Inc.

25 Brush Street

Pontiac, MI 48341

(248)-627-0400

**IN CASE OF EMERGENCY (HEALTH OR SPILLS):**

CHEMTREC (US and Canada) (800) 424-9300

Product no. : 67190

Product - Class : Cetol SRD Semi Transparent Stain

Customer Part Number :

Customer ShipTo ID :

## 2 . Hazards identification

Physical state : Liquid.

Emergency overview : DANGER !

FLAMMABLE LIQUID AND VAPOR. COMBUSTIBLE. CAUSES EYE AND SKIN BURNS. HARMFUL IF SWALLOWED. CAUSES RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF ABSORBED THROUGH SKIN. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. SUSPECT CANCER HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE CANCER.

Keep away from heat, sparks and flame. Do not breathe vapor or mist. Do not ingest. Do not get in eyes or on skin or clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

### Potential acute health effects

**Inhalation** : Irritating to respiratory system.

Other effects of inhalation may include: anesthesia, CNS effects, confusion, depression, dizziness, drowsiness, fatigue, headache, incoordination, nausea, pulmonary edema, weakness,

**Ingestion** : Toxic if swallowed. May cause burns to mouth, throat and stomach.

Other effects of ingestion may include : CNS effects, diarrhea, dizziness, drowsiness, fatigue, headache, incoordination, irritation, nausea, vomiting, weakness,

**Skin** : Corrosive to the skin. Causes burns. Harmful in contact with skin.

Other effects of skin contact may include: defatting, dehydration, dermatitis, discoloration,

Effects due to absorption through skin may include: dizziness, headache, nausea, weakness,

**Eyes** : Corrosive to eyes. Causes burns.

Other effects of eye contact may include : burning, eye damage, redness, swelling, tearing,

### Potential chronic health effects

## 2. Hazards identification

CARCINOGENIC EFFECTS: Classified 2B (Possible for humans.) by IARC [cobalt bis (2-ethylhexanoate)]. Classified SUSPECTED by Raw Material Supplier [2-ethylhexyl alcohol]. Classified 2B (Possible for humans.) by IARC [ethylbenzene]. Classified 2B (Possible for humans.) by IARC [naphthalene]. Classified 2 (Reasonably anticipated to be human carcinogens.) by NTP [naphthalene].  
 MUTAGENIC EFFECTS: No known significant effects or critical hazards.  
 TERATOGENIC EFFECTS: Classified POSSIBLE for humans [cyclohexanone].  
 Classified POSSIBLE for humans [ethylbenzene].

**Target organs** : Contains material which may cause damage to the following organs: blood, kidneys, lungs, the reproductive system, liver, heart, cardiovascular system, bone marrow, central nervous system (CNS).

**Medical conditions aggravated by over-exposure** : skin disorders, eye disorders, respiratory conditions,

NOTICE: Reports have associated repeated and prolonged OVEREXPOSURE to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents of this package may be harmful or fatal.

See toxicological information (section 11)

## 3. Composition/information on ingredients

Name	CAS number	% by weight	Vapor pressure	Exposure limits
heat bodied linseed oil	67746-08-1	25 - 35	Not available.	
linseed alkyd	.....	10 - 25	Not available.	
aliphatic solvent stabilizer	..... 127519-17-9	10 - 25 5 - 10	Not available.	
synthetic amorphous silica	7631-86-9	1 - 5	Not available.	<b>OSHA PEL (United States).</b> TWA: 80 mg/m <sup>3</sup> 8 hour(s). <b>ACGIH TLV (United States).</b> TWA: 10 mg/m <sup>3</sup> 8 hour(s).
glycol ethers	.....	1 - 5	Not available.	<b>ACGIH TLV (United States). Skin</b> TWA: 5 ppm 8 hour(s).
aliphatic hydrocarbon	64742-47-8	1 - 5	0.023 kPa (0.17 mm Hg)	
aromatic solvent	.....	1 - 5	Not available.	<b>ACGIH TLV (United States).</b> TWA: 100 ppm 8 hour(s).
1,2,4-trimethylbenzene	95-63-6	1 - 5	Not available.	<b>ACGIH TLV (United States).</b> TWA: 25 ppm 8 hour(s).
alkyloaminoamide	.....	1 - 5	Not available.	
aliphatic hydrocarbon	8052-41-3	1 - 5	0.27 kPa (2 mm Hg)	<b>OSHA PEL (United States).</b> TWA: 500 ppm 8 hour(s). <b>ACGIH TLV (United States).</b> TWA: 100 ppm 8 hour(s).
iodo-propynyl butyl carbamate	55406-53-6	1 - 5	Not available.	
xylene, mixed isomers	1330-20-7	1 - 5	0.68 kPa (5.1 mm Hg)	<b>OSHA PEL (United States).</b> TWA: 100 ppm 8 hour(s). <b>ACGIH TLV (United States).</b> TWA: 100 ppm 8 hour(s). STEL: 150 ppm 15 minute(s).
zirconium carboxylate	22464-99-9	1 - 5	Not available.	<b>ACGIH TLV (United States).</b> TWA: 5 mg/m <sup>3</sup> 8 hour(s). TWA: 5 mg/m <sup>3</sup> 8 hour(s).
light stabilizer	.....	0.1 - 1	Not available.	
cobalt bis (2-ethylhexanoate)	136-52-7	0.1 - 1	Not available.	
ethylbenzene	100-41-4	0.1 - 1	0.95 kPa (7.1 mm Hg)	<b>OSHA PEL (United States).</b> TWA: 100 ppm 8 hour(s). <b>ACGIH TLV (United States).</b> TWA: 100 ppm 8 hour(s). STEL: 125 ppm 15 minute(s).
naphthalene	91-20-3	0.1 - 1	Not available.	<b>OSHA PEL (United States).</b> TWA: 10 ppm 8 hour(s). <b>ACGIH TLV (United States). Skin</b>

### 3 . Composition/information on ingredients

TWA: 10 ppm 8 hour(s).  
STEL: 15 ppm 15 minute(s).

There are no ingredients or additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### 4 . First aid measures

- Eye contact** : Get medical attention immediately if symptoms occur. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Chemical burns must be treated promptly by a physician.
- Skin contact** : Get medical attention immediately if symptoms occur. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Inhalation** : Get medical attention immediately if symptoms occur. Move exposed person to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Ingestion** : Get medical attention immediately. Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### 5 . Fire-fighting measures

- Flammability of the product** : Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.  
DANGER - Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container. Waste should be understood to include contaminated articles, including spray booth filters and strippings.
- Auto-ignition temperature** : Not available.
- Flash point** : Closed cup: 45.556°C (114°F) [Setaflash.]
- Flammable limits** : Not available.
- Extinguishing media**
- Suitable** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Not suitable** : Do not use water jet.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
nitrogen oxides  
sulfur oxides  
halogenated compounds  
metal oxide/oxides

## 5 . Fire-fighting measures

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Special remarks on fire hazards** : Not available.

## 6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.


## 7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container. Do not enter confined spaces unless adequately ventilated.
- Storage** : Store in accordance with local regulations. Store in approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## 8 . Exposure controls/personal protection

- Engineering measures** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Personal protection** Selection of personal protective equipment (PPE) is to be established by the employer performing a PPE hazard assessment.

## 8 . Exposure controls/personal protection

<b>Respiratory</b>	: Use properly fitted respiratory protection complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
<b>Hands</b>	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
<b>Eyes</b>	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Recommended: safety glasses with side-shields
<b>Skin</b>	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
<b>Other protection</b>	: Not available.
<b>Personal protective equipment (Pictograms)</b>	: 

## 9 . Physical and chemical properties

<b>Physical state</b>	: Liquid.
<b>Color</b>	: Not available.
<b>Odor</b>	: Not available.
<b>Taste</b>	: Not available.
<b>Molecular weight</b>	: Not applicable.
<b>Molecular formula</b>	: Not applicable.
<b>pH</b>	: Not available.
<b>Boiling/condensation point</b>	: Not available.
<b>Melting/freezing point</b>	: Not available.
<b>Critical temperature</b>	: Not available.
<b>Relative density</b>	: Not available.
<b>Vapor density</b>	: Heavier than air
<b>Volatility</b>	: 40.354% (v/v), 41.045% (w/w)
<b>Odor threshold</b>	: Not available.
<b>Evaporation rate</b>	: Highest known value: Less than 1. (p-Chlorobenzotrifluoride) compared with butyl acetate
<b>Viscosity</b>	: Not available.
<b>Ionicity (in water)</b>	: Not available.
<b>Dispersibility properties</b>	: Not available.
<b>Solubility</b>	: Not available.

## 10 . Stability and reactivity

<b>Stability</b>	: The product is stable, under normal conditions of storage and use.
<b>Conditions to avoid</b>	: heat, open flame, sparks, freezing, light, avoid x-rays or uv radiation, dusty conditions,
<b>Materials to avoid</b>	: Reactive or incompatible with the following materials: oxidizing materials, metals, acids and alkalis.
<b>Hazardous decomposition products</b>	: Not available.
<b>Hazardous polymerization</b>	: Will not undergo hazardous polymerization.

## 11 . Toxicological information

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
light stabilizer	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
aromatic solvent	LD50 Dermal	Rat	>2000 mg/kg	-
	LC50 Inhalation	Rat	>590 mg/m3	4 hours
	Vapor			
alkyloaminoamide xylene, mixed isomers	LD50 Oral	Rat	>2000 mg/kg	-
	LD50 Dermal	Rabbit	>1700 mg/kg	-
	LD50 Oral	Rat	4300 mg/kg	-
	LC50 Inhalation	Rat	5000 ppm	4 hours
1,2,4-trimethylbenzene	Vapor			
	LD50 Dermal	Rabbit	>3160 mg/kg	-
	LD50 Oral	Rat	3400 mg/kg	-
	LC50 Inhalation	Rat	18000 mg/m3	4 hours
synthetic amorphous silica	Vapor			
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5110 mg/kg	-
	LC50 Inhalation	Rat	>139 mg/m3	14 hours
iodo-propynyl butyl carbamate	Dusts and mists			
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	1056 mg/kg	-
	LC50 Inhalation	Rat	680 mg/m3	4 hours
ethylbenzene	Dusts and mists			
	LD50 Dermal	Rabbit	15486 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-
	LC50 Inhalation	Rat	55000 mg/m3	2 hours
naphthalene	Vapor			
	LD50 Dermal	Rabbit	>20000 mg/kg	-
	LD50 Oral	Rat	490 mg/kg	-
	LC50 Inhalation	Rat	>340 mg/m3	1 hours
	Dusts and mists			

## 12 . Ecological information

**Environmental effects** : No known significant effects or critical hazards.

### Aquatic ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure	
xylene, mixed isomers	Mortality	Acute LC50 13.4 mg/L	Fish	96 hours	
	Mortality	Acute LC50 13.3 mg/L	Fish	96 hours	
	Mortality	Acute LC50 12 mg/L	Fish	96 hours	
	Mortality	Acute LC50 8.6 mg/L	Fish	96 hours	
	Mortality	Acute LC50 8.2 mg/L	Fish	96 hours	
	Mortality	Acute LC50 3.3 mg/L	Fish	96 hours	
1,2,4-trimethylbenzene	Mortality	Acute LC50 7.72 mg/L	Fish	96 hours	
	Mortality	Acute LC50 2.9 mg/L	Fish	96 hours	
aliphatic hydrocarbon iodo-propynyl butyl carbamate	Mortality	Acute LC50 2.9 mg/L	Fish	96 hours	
	Intoxication	Acute EC50 0.956 mg/L	Daphnia	48 hours	
	Intoxication	Acute EC50 0.16 mg/L	Daphnia	48 hours	
	Mortality	Acute LC50 0.2 mg/L	Fish	96 hours	
	Mortality	Acute LC50 0.1 mg/L	Fish	96 hours	
	Mortality	Acute LC50 0.072 mg/L	Fish	96 hours	
	Mortality	Acute LC50 0.067 mg/L	Fish	96 hours	
	ethylbenzene	Population	Acute EC50 7.2 mg/L	Algae	48 hours
		Intoxication	Acute EC50 2.97 mg/L	Daphnia	48 hours
		Intoxication	Acute EC50 2.93 mg/L	Daphnia	48 hours
		Mortality	Acute LC50 4.2 mg/L	Fish	96 hours
Mortality		Acute LC50 9.09 mg/L	Fish	96 hours	
naphthalene	Mortality	Acute LC50 9.6 mg/L	Fish	96 hours	
	Intoxication	Acute EC50 2.55 mg/L	Daphnia	48 hours	
	Intoxication	Acute EC50 2.194 mg/L	Daphnia	48 hours	
	Intoxication	Acute EC50 1.6 mg/L	Daphnia	48 hours	

## 12 . Ecological information

Mortality	Acute LC50 1.8 mg/L	Fish	96 hours
Mortality	Acute LC50 1.6 mg/L	Fish	96 hours
Mortality	Acute LC50 1 mg/L	Daphnia	96 hours

**Conclusion/Summary** : Not available.

### Biodegradability

**Other adverse effects** : No known significant effects or critical hazards.





## 13 . Disposal considerations

**Waste disposal** : The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**Disposal should be in accordance with applicable regional, national and local laws and regulations.**

## 14 . Transport information

**Note:** Information contained in this section may vary from the actual shipping description depending on quantity in containers, mode of shipment and use of exemptions.

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
<b>DOT Classification</b>	UN1263	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)	3	III		RQ: 7477.25lbs (3391.04kgs) [xylene, mixed isomers]
<b>TDG Classification</b>	UN1263	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)	3	III		
<b>IMDG Class</b>	1263	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)	3	III		
<b>IATA-DGR Class</b>	1263	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)	3	III		

PG\* : Packing group

## 15 . Regulatory information

### United States

**U.S. Federal regulations** : **United States inventory (TSCA 8b):** All components in this product have been verified as being on the TSCA Inventory.

### International regulations

**International lists** : This product contains one or more components that are NOT listed on the CEPA DSL inventory.

\*\* All values in this section reported as percentage by weight, unless otherwise specified.

## 16 . Other information

HMIS III ® Hazardous  
Material Information System  
(U.S.A.)

Health	*	2
Flammability		2
Physical hazards		0
Personal protection		

Caution: HMIS III ® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risk, and 4 representing severe hazards or risk. Although HMIS III ® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS III ® ratings are to be used with a fully implemented HMIS III ® program. HMIS III ® is a registered mark of the National Paint & Coatings Association (NPCA).

The customer is responsible for determining the PPE code for this material.

WHMIS (Canada)



Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).

Class D-1B: Material causing immediate and serious toxic effects (Toxic).

Class D-2A: Material causing other toxic effects (Very toxic).

Class E: Corrosive material

Other special considerations : Not available.

### Notice to reader

**IMPORTANT NOTE** The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.