

SIK29003 BL INT. CLEAR SATIN

SECTION 1

PRODUCT IDENTIFIER SIK29003 BL INT. CLEAR SATIN
 DATE OF PREPARATION APRIL 8, 2010
 PRODUCT USE PROTECTIVE COATING
 MANUFACTURED BY: AKZO NOBEL PAINTS LLC, 15885 WEST SPRAGUE ROAD,
 STRONGSVILLE, OHIO 44136, U.S.A
 ICI PAINTS (CANADA), 8200 KEELE STREET,
 CONCORD, ONTARIO L4K 2A5, CANADA.
 EMERGENCY AND MSDS TELEPHONE NUMBER:
 1-800-545-2643
 MSDS PREPARED BY: PRODUCT SAFETY AND COMPLIANCE DEPARTMENT
 AKZO NOBEL PAINTS LLC

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	WT. %:
CHEMICAL NAME STYRENE ACRYLIC COPOLYMER	20-30
COMMON NAME : STYRENE ACRYLIC COPOLYMER	
CAS NUMBER: CONFIDENTIAL	
CHEMICAL NAME URETHANE ACRYLIC RESIN	1-5
COMMON NAME : URETHANE ACRYLIC RESIN	
CAS NUMBER: CONFIDENTIAL	
CHEMICAL NAME 2-PROPANOL,1-(2-BUTOXY-1-METHYLETHOXY)-	1-5
COMMON NAME : DIPROPYLENE GLYCOL BUTYL ETHER	
CAS NUMBER: 29911-28-2	
CHEMICAL NAME PROPANOL, (2-METHOXYMETHYLETHOXY)-	1-5
COMMON NAME : DPG MONOMETHYL ETHER	
CAS NUMBER: 34590-94-8	
CHEMICAL NAME 1,2-PROPANEDIOL	1-5
COMMON NAME : PROPYLENE GLYCOL	
CAS NUMBER: 57-55-6	
CHEMICAL NAME SILICA	1-5
COMMON NAME : AMORPHOUS SILICA	
CAS NUMBER: 7631-86-9	
CHEMICAL NAME WATER	60-70
COMMON NAME : WATER	
CAS NUMBER: 7732-18-5	

SECTION 3: HAZARDS IDENTIFICATION

PRIMARY ROUTE(S) OF EXPOSURE

INHALATION, SKIN CONTACT, EYE CONTACT, INGESTION.

EFFECTS OF OVEREXPOSURE

INHALATION PROLONGED INHALATION MAY LEAD TO DROWSINESS, DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, CENTRAL NERVOUS SYSTEM DEPRESSION, ANESTHETIC EFFECT OR NARCOSIS, LIVER DAMAGE.

SKIN CONTACT IRRITATION OF SKIN. PROLONGED OR REPEATED CONTACT CAN CAUSE DERMATITIS. POSSIBLE SENSITIZATION TO SKIN. SKIN CONTACT MAY RESULT IN DERMAL ABSORPTION OF COMPONENT(S) OF THIS PRODUCT WHICH MAY CAUSE DROWSINESS, DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, CENTRAL NERVOUS SYSTEM DEPRESSION, ANESTHETIC EFFECT OR NARCOSIS, KIDNEY DAMAGE.

EYE CONTACT IRRITATION OF EYES. PROLONGED OR REPEATED CONTACT CAN CAUSE CONJUNCTIVITIS, TEARING OF EYES.

INGESTION INGESTION MAY CAUSE MOUTH AND THROAT IRRITATION, DROWSINESS, DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION, VOMITING, CENTRAL NERVOUS SYSTEM DEPRESSION, LIVER DAMAGE, KIDNEY DAMAGE.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

EYE, SKIN, RESPIRATORY DISORDERS, LIVER DISORDERS.

SECTION 4: FIRST-AID MEASURES

INHALATION REMOVE TO FRESH AIR. RESTORE AND SUPPORT CONTINUED BREATHING.

GET EMERGENCY MEDICAL ATTENTION.

HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. GET MEDICAL HELP FOR ANY BREATHING DIFFICULTY.

SKIN CONTACT WASH THOROUGHLY WITH SOAP AND WATER. IF ANY PRODUCT REMAINS, GENTLY RUB PETROLEUM JELLY, VEGETABLE OR MINERAL/BABY OIL ONTO SKIN. REPEATED APPLICATIONS MAY BE NEEDED. REMOVE CONTAMINATED CLOTHING.

WASH CONTAMINATED CLOTHING BEFORE RE-USE.

EYE CONTACT FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS FOR AT LEAST 15 MINUTES. IF IRRITATION OR OTHER EFFECTS PERSIST, OBTAIN MEDICAL TREATMENT.

INGESTION IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

SECTION 5: FIRE-FIGHTING MEASURES

FLASH POINT (SETA) 160 F./ 71 C. **LOWER EXPLOSIVE LIMIT** 2.6 (%)
UPPER EXPLOSIVE LIMIT 12.6 (%)

FIRE EXTINGUISHING MEDIA

DRY CHEMICAL OR FOAM

WATER FOG.

CARBON DIOXIDE.

UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT OR FIRE.

VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL LONG DISTANCES TO A SOURCE OF IGNITION AND FLASH BACK.

VAPORS CAN FORM EXPLOSIVE MIXTURES IN AIR AT ELEVATED TEMPERATURES.

MAY DECOMPOSE UNDER FIRE CONDITIONS EMITTING IRRITANT AND/OR TOXIC GASES.

FIRE FIGHTING PROCEDURES

WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS.

FIREFIGHTERS SHOULD USE FULL PROTECTIVE CLOTHING, EYE PROTECTION, AND SELF-CONTAINED BREATHING APPARATUS.

HAZARDOUS DECOMPOSITION OR COMBUSTION PRODUCTS

CARBON MONOXIDE, CARBON DIOXIDE, TOXIC GASES.

PROPIONALDEHYDE.

SECTION 6 ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS.

ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA. SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS. EVACUATE ALL UNNECESSARY PERSONNEL. PLACE COLLECTED MATERIAL IN PROPER CONTAINER. COMPLETE PERSONAL PROTECTIVE EQUIPMENT MUST BE USED DURING CLEANUP.

LARGE SPILLS - SHUT OFF LEAK IF SAFE TO DO SO. DIKE AND CONTAIN SPILL. PUMP TO STORAGE OR SALVAGE VESSELS. USE ABSORBENT TO PICK UP EXCESS RESIDUE. KEEP SALVAGEABLE MATERIAL AND RINSE WATER OUT OF SEWERS AND WATER COURSES.

SMALL SPILLS - USE ABSORBENT TO PICK UP RESIDUE AND DISPOSE OF PROPERLY.

SECTION 7 HANDLING AND STORAGE

HANDLING AND STORAGE

STORE BELOW 100F (38C). KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. KEEP FROM FREEZING.

OTHER PRECAUTIONS USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND

EYES, AND BREATHING OF VAPORS. WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING.
KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE.
EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

COMMON NAME : DPG MONOMETHYL ETHER

CAS NUMBER: 34590-94-8

ACGIH(TWA): SKIN 100 PPM OSHA(TWA): 100 PPM

ACGIH(STEL): 150 PPM

OSHA((SKIN) : SKIN CEILING: SUPP REC STD.: NOT AVAILABLE

COMMON NAME : AMORPHOUS SILICA

CAS NUMBER: 7631-86-9

ACGIH(TWA): 10 MG/M3 OSHA(TWA): 6 MG/M3

SKIN - DENOTES THAT ADDITIONAL EXPOSURE, OVER AND ABOVE AIRBORNE EXPOSURE, MAY RESULT FROM SKIN ABSORPTION.

RESPIRATORY PROTECTION

CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE EXPOSURE STANDARDS WHEN USING THIS MATERIAL. WHEN RESPIRATORY PROTECTION IS DETERMINED TO BE NECESSARY, USE A NIOSH/MSHA (CANADIAN Z94.4) APPROVED ELASTOMERIC SEALING-SURFACE FACEPIECE RESPIRATOR OUTFITTED WITH ORGANIC VAPOR CARTRIDGES AND PAINT SPRAY (DUST/MIST) PREFILTERS.

DETERMINE THE PROPER LEVEL OF PROTECTION BY CONDUCTING APPROPRIATE AIR MONITORING. CONSULT 29CFR1910.134 FOR SELECTION OF RESPIRATORS (CANADIAN Z94.4).

VENTILATION PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.

PERSONAL PROTECTIVE EQUIPMENT

EYE WASH, SAFETY SHOWER, SAFETY GLASSES OR GOGGLES.
IMPERVIOUS GLOVES, IMPERVIOUS CLOTHING, APRON.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE: NOT AVAILABLE SPECIFIC GRAVITY: 1.027

BOILING RANGE (F/C): 212-380/100-193 WEIGHT PER GALLON: 8.56/ 10.28IMP

%VOLATILE BY VOLUME: 75.30

PHYSICAL STATE: LIQUID APPEARANCE CLEAR

SOLUBILITY IN WATER: NOT AVAILABLE PH: NOT AVAILABLE

SECTION 10: STABILITY AND REACTIVITY

UNDER NORMAL CONDITIONS

STABLE

SEE SECTION 5 FIRE FIGHTING MEASURES

MATERIALS TO AVOID

OXIDIZERS, NITRIC ACID, HYDROFLUORIC ACID, COMBUSTIBLE MATERIALS.

CONDITIONS TO AVOID

ELEVATED TEMPERATURES, CONTACT WITH OXIDIZING AGENT, FREEZING, SPARKS, OPEN FLAME, IGNITION SOURCES.

HAZARDOUS POLYMERIZATION

WILL NOT OCCUR

SECTION 11: TOXICOLOGICAL INFORMATION

COMMON NAME : URETHANE ACRYLIC RESIN

CAS NUMBER: CONFIDENTIAL

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME : DIPROPYLENE GLYCOL BUTYL ETHER

CAS NUMBER: 29911-28-2

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

LD50:>2000.00 MG/KG SKN RBT

LD50: 4400.00 MG/KG ORL RAT

COMMON NAME : DPG MONOMETHYL ETHER

CAS NUMBER: 34590-94-8

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

LD50: 5.40 ML/KG ORL RAT

LD50: 10.00 ML/KG SKN RBT

COMMON NAME : PROPYLENE GLYCOL

CAS NUMBER: 57-55-6

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

LD50: 20.00 GM/KG ORL RAT

LD50: 20.80 GM/KG SKN RBT

COMMON NAME : AMORPHOUS SILICA

CAS NUMBER: 7631-86-9

CARCINOGENICITY LISTED BY: NTP NO IARC YES 3 OSHA NO ACGIH NO

LD50:>5000.00 MG/KG ORL RAT

LD50:>2000.00 MG/KG SKN RBT

LC50:> 2.20 MG/L/HR IHL RAT

SUPPLEMENTAL HEALTH INFORMATION

CONTAINS A CHEMICAL THAT MAY BE ABSORBED THROUGH SKIN. NOTICE - REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

OTHER EFFECTS OF OVEREXPOSURE MAY INCLUDE TOXICITY TO LIVER, KIDNEY.

CARCINOGENICITY NO CARCINOGENIC EFFECTS ARE ANTICIPATED

REPRODUCTIVE EFFECTS

NO REPRODUCTIVE EFFECTS ARE ANTICIPATED

MUTAGENICITY NO MUTAGENIC EFFECTS ARE ANTICIPATED

TERATOGENICITY NO TERATOGENIC EFFECTS ARE ANTICIPATED

SECTION 12: ECOLOGICAL INFORMATION

NO ECOLOGICAL TESTING HAS BEEN DONE BY AKZO NOBEL PAINTS LLC ON THIS PRODUCT AS A WHOLE.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

SECTION 14: TRANSPORT INFORMATION

DOT	UN1263, PAINT, COMBUSTIBLE LIQUID, PGIII
IMDG	NOT AVAILABLE
IATA	NOT AVAILABLE
TDG	NOT AVAILABLE

SECTION 15: REGULATORY INFORMATION

SARA SARA CERCLA HAZ AIR MARINE

302 313 302.4 POLLUTANT POLTNT

THIS PRODUCT CONTAINS NO SARA 302, CERCLA 302.4 OR HAZARDOUS AIR POLLUTANT CHEMICALS. IT ALSO CONTAINS NO CHEMICALS WHICH ARE SUBJECT TO THE REPORTING REQUIREMENTS UNDER SARA 313.

AS OF THE DATE OF THIS MSDS, ALL OF THE COMPONENTS IN THIS PRODUCT ARE LISTED (OR ARE OTHERWISE EXEMPT FROM LISTING) ON THE TSCA INVENTORY.

THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR (CONTROLLED PRODUCTS REGULATIONS) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

SECTION 16: OTHER INFORMATION

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE AT THE TIME OF PREPARATION OF THIS DATA SHEET AND WHICH AKZO NOBEL PAINTS LLC BELIEVES TO BE RELIABLE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA. AKZO NOBEL PAINTS LLC SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS INFORMATION, OR OF ANY PRODUCT, METHOD OR APPARATUS MENTIONED AND YOU MUST MAKE YOUR OWN DETERMINATION OF ITS SUITABILITY AND COMPLETENESS FOR YOUR OWN USE, FOR THE PROTECTION OF THE ENVIRONMENT, AND THE HEALTH AND SAFETY OF YOUR EMPLOYEES AND USERS OF THIS MATERIAL.

**COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD
29CFR1910.1200.**