



-----  
SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS  
-----

COMMON NAME :	TITANIUM DIOXIDE	
CAS NUMBER:	13463-67-7	
CHEMICAL NAME	HEXANOIC ACID, 2-ETHYL-, COBALT(2+) SALT	.1-1.0
COMMON NAME :	COBALT ALKANOATE	
CAS NUMBER:	136-52-7	
CHEMICAL NAME	DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	5-10
COMMON NAME :	HYDROTREATED LIGHT DISTILLATE	
CAS NUMBER:	64742-47-8	
CHEMICAL NAME	NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY	20-30
COMMON NAME :	NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY	
CAS NUMBER:	64742-82-1	
CHEMICAL NAME	SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC	1-5
COMMON NAME :	LIGHT AROMATIC SOLVENT NAPHTHA	
CAS NUMBER:	64742-95-6	
CHEMICAL NAME	LINSEED OIL, POLYMERIZED	10-20
COMMON NAME :	LINSEED OIL	
CAS NUMBER:	67746-08-1	
CHEMICAL NAME	STODDARD SOLVENT	5-10
COMMON NAME :	MINERAL SPIRITS	
CAS NUMBER:	8052-41-3	
CHEMICAL NAME	ETHENE, HOMOPOLYMER	1-5
COMMON NAME :	POLYETHYLENE	
CAS NUMBER:	9002-88-4	
CHEMICAL NAME	BENZENE, 1,2,4-TRIMETHYL-	1-5
COMMON NAME :	PSEUDOCUMENE	
CAS NUMBER:	95-63-6	
CHEMICAL NAME	BENZENE, (1-METHYLETHYL) -	.1-1.0
COMMON NAME :	CUMENE	
CAS NUMBER:	98-82-8	

---

SECTION 3: HAZARDS IDENTIFICATION

---

## PRIMARY ROUTE(S) OF EXPOSURE

INHALATION, SKIN CONTACT, EYE CONTACT, INGESTION.

## EFFECTS OF OVEREXPOSURE

## INHALATION

PROLONGED INHALATION MAY LEAD TO LOSS OF APPETITE, MUCOUS MEMBRANE IRRITATION, FATIGUE, DROWSINESS, DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, VOMITING, BLURRED VISION, DIFFICULTY WITH SPEECH, CENTRAL NERVOUS SYSTEM DEPRESSION, INTOXICATION, CONFUSION, ANESTHETIC EFFECT OR NARCOSIS, DIFFICULTY OF BREATHING, ALLERGIC RESPONSE, ASTHMATIC REACTION, TREMORS, LIVER DAMAGE, KIDNEY DAMAGE, PULMONARY EDEMA, CONVULSIONS, LOSS OF CONSCIOUSNESS, RESPIRATORY FAILURE, ASPHYXIATION, DEATH. POSSIBLE SENSITIZATION TO RESPIRATORY TRACT.

## SKIN CONTACT

IRRITATION OF SKIN. PROLONGED OR REPEATED CONTACT CAN CAUSE DERMATITIS, DEFATTING, BLISTERING. SKIN CONTACT MAY RESULT IN DERMAL ABSORPTION OF COMPONENT(S) OF THIS PRODUCT WHICH MAY CAUSE DROWSINESS, DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, CENTRAL NERVOUS SYSTEM DEPRESSION, CONFUSION, TREMORS, CONVULSIONS.

## EYE CONTACT

IRRITATION OF EYES. PROLONGED OR REPEATED CONTACT CAN CAUSE CONJUNCTIVITIS, BLURRED VISION, TEARING OF EYES, REDNESS OF EYES, SEVERE EYE IRRITATION.

## INGESTION

INGESTION MAY CAUSE LUNG INFLAMMATION AND DAMAGE DUE TO ASPIRATION OF MATERIAL INTO LUNGS, MOUTH AND THROAT IRRITATION, MUCOUS MEMBRANE IRRITATION, DROWSINESS, DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, VOMITING, DIARRHEA, GASTRO-INTESTINAL DISTURBANCES, CENTRAL NERVOUS SYSTEM DEPRESSION, DIFFICULTY OF BREATHING, LIVER DAMAGE, KIDNEY DAMAGE, PULMONARY EDEMA, CONVULSIONS, LOSS OF CONSCIOUSNESS, DEATH.

---

---

SECTION 3: HAZARDS IDENTIFICATION

---

---

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE  
EYE, SKIN, RESPIRATORY DISORDERS, KIDNEY DISORDERS, LIVER  
DISORDERS.

---

---

SECTION 4: FIRST-AID MEASURES

---

---

INHALATION REMOVE TO FRESH AIR. RESTORE AND SUPPORT CONTINUED  
BREATHING.  
GET EMERGENCY MEDICAL ATTENTION.  
HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. GET MEDICAL  
HELP FOR ANY BREATHING DIFFICULTY.  
REMOVE TO FRESH AIR IF INHALATION CAUSES EYE WATERING,  
HEADACHES, DIZZINESS, OR OTHER DISCOMFORT.

SKIN CONTACT WASH THOROUGHLY WITH SOAP AND WATER. IF ANY PRODUCT REMAINS,  
GENTLY RUB PETROLEUM JELLY, VEGETABLE OR MINERAL/BABY OIL  
ONTO SKIN. REPEATED APPLICATIONS MAY BE NEEDED. REMOVE  
CONTAMINATED CLOTHING.  
WASH CONTAMINATED CLOTHING BEFORE RE-USE.

EYE CONTACT FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER, ESPECIALLY  
UNDER LIDS FOR AT LEAST 15 MINUTES. IF IRRITATION OR OTHER  
EFFECTS PERSIST, OBTAIN MEDICAL TREATMENT.

INGESTION IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

---

---

SECTION 5: FIRE-FIGHTING MEASURES

---

---

FLASH POINT (SETA) 115 F./ 46 C. LOWER EXPLOSIVE LIMIT 1.1 (%)  
UPPER EXPLOSIVE LIMIT 6.0 (%)

FIRE EXTINGUISHING MEDIA  
DRY CHEMICAL OR FOAM  
WATER FOG.  
CARBON DIOXIDE.

---

SECTION 5: FIRE-FIGHTING MEASURES

---

UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT OR FIRE.

VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL LONG DISTANCES TO A SOURCE OF IGNITION AND FLASH BACK.

VAPORS CAN FORM EXPLOSIVE MIXTURES IN AIR AT ELEVATED TEMPERATURES.

CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

MAY DECOMPOSE UNDER FIRE CONDITIONS EMITTING IRRITANT AND/OR TOXIC GASES.

RAGS, STEEL WOOL OR WASTE SOAKED WITH THIS MATERIAL MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED.

IMMEDIATELY AFTER USE, PLACE SOAKED RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.

FIRE FIGHTING PROCEDURES

WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS. FIREFIGHTERS SHOULD USE FULL PROTECTIVE CLOTHING, EYE PROTECTION, AND SELF-CONTAINED BREATHING APPARATUS.

HAZARDOUS DECOMPOSITION OR COMBUSTION PRODUCTS

CARBON MONOXIDE, CARBON DIOXIDE, FORMALDEHYDE, ACROLEIN, ALDEHYDES, TOXIC GASES.

---

SECTION 6 ACCIDENTAL RELEASE MEASURES

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS.

ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA.

VENTILATE AREA WITH EXPLOSION-PROOF EQUIPMENT. SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS. EVACUATE ALL

UNNECESSARY PERSONNEL. PLACE COLLECTED MATERIAL IN PROPER CONTAINER. SPILLED MATERIAL IS EXTREMELY SLIPPERY. COMPLETE

PERSONAL PROTECTIVE EQUIPMENT MUST BE USED DURING CLEANUP.

LARGE SPILLS - SHUT OFF LEAK IF SAFE TO DO SO. DIKE AND

CONTAIN SPILL. PUMP TO STORAGE OR SALVAGE VESSELS. USE

ABSORBENT TO PICK UP EXCESS RESIDUE. KEEP SALVAGEABLE

-----  
 SECTION 6 ACCIDENTAL RELEASE MEASURES  
 -----

MATERIAL AND RINSE WATER OUT OF SEWERS AND WATER COURSES.  
 SMALL SPILLS - USE ABSORBENT TO PICK UP RESIDUE AND DISPOSE  
 OF PROPERLY.

-----  
 SECTION 7 HANDLING AND STORAGE  
 -----

HANDLING AND STORAGE

STORE BELOW 100F (38C). KEEP AWAY FROM HEAT, SPARKS AND  
 OPEN FLAME. KEEP FROM FREEZING.

OTHER PRECAUTIONS USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY.  
 KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND  
 EYES, AND BREATHING OF VAPORS. WASH HANDS THOROUGHLY AFTER  
 HANDLING, ESPECIALLY BEFORE EATING OR SMOKING.  
 KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE.  
 EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES.  
 GROUND EQUIPMENT WHEN TRANSFERRING TO PREVENT ACCUMULATION  
 OF STATIC CHARGE.  
 AVOID SPONTANEOUS COMBUSTION OF CONTAMINATED RAGS AND OTHER  
 EASILY IGNITABLE ORGANIC ACCUMULATIONS.

-----  
 SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION  
 -----

COMMON NAME : ETHYLBENZENE

CAS NUMBER: 100-41-4

ACGIH (TWA) : 100 PPM

ACGIH (STEL) : 125 PPM

OSHA (TWA) : 100 PPM

COMMON NAME : XYLENE

CAS NUMBER: 1330-20-7

ACGIH (TWA) : 100 PPM

ACGIH (STEL) : 150 PPM

OSHA (TWA) : 100 PPM

COMMON NAME : TITANIUM DIOXIDE

CAS NUMBER: 13463-67-7

ACGIH (TWA) : 10 MG/M3

OSHA (TWA) : 10 MG/M3

COMMON NAME : COBALT ALKANOATE

-----  
 SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION  
 -----

CAS NUMBER:	136-52-7				
ACGIH (TWA):	.02	MG/M3	OSHA (TWA):	.05	MG/M3
COMMON NAME :	HYDROTREATED LIGHT DISTILLATE				
CAS NUMBER:	64742-47-8				
ACGIH (TWA):	100	PPM	OSHA (TWA):	100	PPM
COMMON NAME :	LIGHT AROMATIC SOLVENT NAPHTHA				
CAS NUMBER:	64742-95-6				
			OSHA (TWA):	500X	PPM
COMMON NAME :	LINSEED OIL				
CAS NUMBER:	67746-08-1				
			OSHA (TWA):	5	MG/M3
COMMON NAME :	MINERAL SPIRITS				
CAS NUMBER:	8052-41-3				
ACGIH (TWA):	100	PPM	OSHA (TWA):	500	PPM
COMMON NAME :	CUMENE				
CAS NUMBER:	98-82-8				
ACGIH (TWA):	50	PPM	OSHA (TWA):	50	PPM
OSHA ( SKIN)	: SKIN CEILING:		SUPP REC STD.:	NOT AVAILABLE	

X AS PETROLEUM DISTILLATES

## RESPIRATORY PROTECTION

CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE EXPOSURE STANDARDS WHEN USING THIS MATERIAL. WHEN RESPIRATORY PROTECTION IS DETERMINED TO BE NECESSARY, USE A NIOSH/MSHA (CANADIAN Z94.4) APPROVED ELASTOMERIC SEALING-SURFACE FACEPIECE RESPIRATOR OUTFITTED WITH ORGANIC VAPOR CARTRIDGES AND PAINT SPRAY (DUST/MIST) PREFILTERS. DETERMINE THE PROPER LEVEL OF PROTECTION BY CONDUCTING APPROPRIATE AIR MONITORING. CONSULT 29CFR1910.134 FOR SELECTION OF RESPIRATORS (CANADIAN Z94.4).

-----  
SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION  
-----

VENTILATION PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT  
BUILD-UP OF VAPORS.  
USE EXPLOSION-PROOF EQUIPMENT.

## PERSONAL PROTECTIVE EQUIPMENT

EYE WASH, SAFETY SHOWER, SAFETY GLASSES OR GOGGLES.  
IMPERVIOUS GLOVES, IMPERVIOUS CLOTHING, FACE SHIELD.

-----  
SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES  
-----

VAPOR PRESSURE:	NOT AVAILABLE	SPECIFIC GRAVITY:	.885
BOILING RANGE (F/C):	277-482/136-250	WEIGHT PER GALLON:	7.37/ 8.85IMP
%VOLATILE BY VOLUME:	63.84		
PHYSICAL STATE:	LIQUID	APPEARANCE	CLEAR
SOLUBILITY IN WATER:	NOT AVAILABLE	PH:	NOT AVAILABLE

-----  
SECTION 10: STABILITY AND REACTIVITY  
-----

## UNDER NORMAL CONDITIONS

STABLE  
STABLE BELOW 212 F (100 C).  
SEE SECTION 5 FIRE FIGHTING MEASURES

## MATERIALS TO AVOID

OXIDIZERS, ACIDS, BASES, HALOGENS, AMINES, NITRIC ACID.  
ACETALDEHYDE

## CONDITIONS TO AVOID

ELEVATED TEMPERATURES, DRIERS, CONTACT WITH OXIDIZING AGENT,  
SPARKS, OPEN FLAME, IGNITION SOURCES.

## HAZARDOUS POLYMERIZATION

WILL NOT OCCUR

-----  
 SECTION 11: TOXICOLOGICAL INFORMATION  
 -----

COMMON NAME : LONG OIL ALKYD RESIN

CAS NUMBER: CONFIDENTIAL

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME : ETHYLBENZENE

CAS NUMBER: 100-41-4

CARCINOGENICITY LISTED BY: NTP NO IARC YES 2B OSHA NO ACGIH YES A3

LD50: 3500.00 MG/KG ORL RAT

LD50: 2272.00 MG/KG IPR MOU

LD50: 17.80 GM/KG SKN RBT

COMMON NAME : XYLENE

CAS NUMBER: 1330-20-7

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

LD50:>1700.00 MG/KG SKN RBT

LD50: 4300.00 MG/KG ORL RAT

LC50: 5000.00 PPM/4HR IHL RAT

COMMON NAME : TITANIUM DIOXIDE

CAS NUMBER: 13463-67-7

CARCINOGENICITY LISTED BY: NTP YES 2B IARC YES 2B OSHA NO ACGIH NO

LD50: 24.00 GM/KG ORL RAT

LC50: 6820.00 MG/M3/4HR IHL RAT

COMMON NAME : COBALT ALKANOATE

CAS NUMBER: 136-52-7

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME : HYDROTREATED LIGHT DISTILLATE

CAS NUMBER: 64742-47-8

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME : NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY

CAS NUMBER: 64742-82-1

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME : LIGHT AROMATIC SOLVENT NAPHTHA

CAS NUMBER: 64742-95-6

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

LD50:> 5.00 GM/KG ORL RAT

-----  
 SECTION 11: TOXICOLOGICAL INFORMATION  
 -----

LC50:>3670.00 PPM IHL RAT

COMMON NAME : LINSEED OIL

CAS NUMBER: 67746-08-1

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME : MINERAL SPIRITS

CAS NUMBER: 8052-41-3

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

LD50:> 3.00 GM/KG SKN RBT

LD50:> 5.00 GM/KG ORL RAT

COMMON NAME : POLYETHYLENE

CAS NUMBER: 9002-88-4

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME : PSEUDOCUMENE

CAS NUMBER: 95-63-6

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

LD50: 5.00 GM/KG ORL RAT

COMMON NAME : CUMENE

CAS NUMBER: 98-82-8

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

LD50: 1400.00 MG/KG ORL RAT

LD50: 12.75 GM/KG ORL MOU

SUPPLEMENTAL HEALTH INFORMATION

CONTAINS A CHEMICAL THAT MAY BE ABSORBED THROUGH SKIN.  
 NOTICE - REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED  
 OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN  
 AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY  
 DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS  
 MAY BE HARMFUL OR FATAL.  
 RAGS, STEEL WOOL OR WASTE SOAKED WITH THIS MATERIAL MAY  
 SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED.  
 IMMEDIATELY AFTER USE, PLACE SOAKED RAGS, STEEL WOOL OR  
 WASTE IN A SEALED WATER-FILLED METAL CONTAINER.  
 OTHER EFFECTS OF OVEREXPOSURE MAY INCLUDE TOXICITY TO LIVER,

-----  
SECTION 11: TOXICOLOGICAL INFORMATION  
-----

## KIDNEY, CENTRAL NERVOUS SYSTEM.

## CARCINOGENICITY

IN LONG TERM (2 YEAR) INHALATION STUDIES, THE NATIONAL TOXICOLOGY PROGRAM (NTP) FOUND CLEAR EVIDENCE OF CARCINOGENIC ACTIVITY IN MICE AND MALE RATS AND SOME EVIDENCE OF CARCINOGENIC ACTIVITY IN FEMALE RATS EXPOSED TO CUMENE.

THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS EVALUATED ETHYLBENZENE AND CLASSIFIED IT AS A POSSIBLE HUMAN CARCINOGEN (GROUP 2B) BASED ON SUFFICIENT EVIDENCE FOR CARCINOGENICITY IN EXPERIMENTAL ANIMALS, BUT INADEQUATE EVIDENCE FOR CANCER IN EXPOSED HUMANS.

IN A 2 YEAR INHALATION STUDY CONDUCTED BY THE NATIONAL TOXICOLOGY PROGRAM (NTP), ETHYLBENZENE VAPOR AT 750 PPM PRODUCED KIDNEY AND TESTICULAR TUMORS IN RATS AND LUNG AND LIVER TUMORS IN MICE. GENETIC TOXICITY STUDIES SHOWED NO GENOTOXIC EFFECTS. THE RELEVANCE OF THESE RESULTS TO HUMANS IS NOT KNOWN.

THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS CLASSIFIED COBALT AND CERTAIN COBALT COMPOUNDS AS POSSIBLY CARCINOGENIC TO HUMANS (GROUP 2B). INJECTION OF METALLIC COBALT, COBALT ALLOYS, AND CERTAIN COBALT COMPOUNDS HAS RESULTED IN THE DEVELOPMENT OF LOCALIZED TUMORS IN LABORATORY ANIMALS.

IN A LIFETIME INHALATION STUDY, EXPOSURE TO 250 MG/M3 TITANIUM DIOXIDE RESULTED IN THE DEVELOPMENT OF LUNG TUMORS IN RATS. THESE TUMORS OCCURRED ONLY AT DUST LEVELS THAT OVERWHELMED THE ANIMALS' LUNG CLEARANCE MECHANISMS AND WERE DIFFERENT FROM COMMON HUMAN LUNG TUMORS IN BOTH TYPE AND LOCATION. THE RELEVANCE OF THESE FINDINGS TO HUMANS IS UNKNOWN BUT QUESTIONABLE.

THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS CLASSIFIED TITANIUM DIOXIDE AS POSSIBLY CARCINOGENIC TO HUMANS (GROUP 2B) BASED ON INADEQUATE EVIDENCE OF CARCINOGENICITY IN HUMANS AND SUFFICIENT EVIDENCE OF CARCINOGENICITY IN EXPERIMENTAL ANIMALS.

CONTAINS METHYL ETHYL KETOXIME (MEKO). IN A LIFETIME, INHALATION STUDY, LIVER CARCINOMAS WERE OBSERVED IN RODENTS EXPOSED TO MEKO. THE RELEVANCE TO HUMANS IS UNKNOWN.

---

---

SECTION 11: TOXICOLOGICAL INFORMATION

---

---

## REPRODUCTIVE EFFECTS

HIGH EXPOSURES TO XYLENE IN SOME ANIMAL STUDIES, OFTEN AT MATERNALLY TOXIC LEVELS, HAVE AFFECTED EMBRYO/FETAL DEVELOPMENT. THE SIGNIFICANCE OF THIS FINDING TO HUMANS IS NOT KNOWN.

## MUTAGENICITY

NO MUTAGENIC EFFECTS ARE ANTICIPATED

## TERATOGENICITY

NO TERATOGENIC EFFECTS ARE ANTICIPATED

---

---

SECTION 12: ECOLOGICAL INFORMATION

---

---

NO ECOLOGICAL TESTING HAS BEEN DONE BY AKZO NOBEL PAINTS LLC ON THIS PRODUCT AS A WHOLE.

---

---

SECTION 13: DISPOSAL CONSIDERATIONS

---

---

## WASTE DISPOSAL

DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

---

---

SECTION 14: TRANSPORT INFORMATION

---

---

DOT UN1263, PAINT, COMBUSTIBLE LIQUID, PGIII

IMDG UN1263, PAINT, CLASS 3, PGIII, LTD QTY (IMDG 3.4.7)  
UN1263, PAINT, CLASS 3, PGIII

IATA NOT AVAILABLE

TDG NOT AVAILABLE

-----  
 SECTION 15: REGULATORY INFORMATION  
 -----

		SARA 302	SARA 313	CERCLA 302.4	HAZ AIR POLLUTANT	MARINE POLTNT
CAS NUMBER:	100-41-4	NO	YES	YES	YES	NO
COMMON NAME :	ETHYLBENZENE					
CAS NUMBER:	1330-20-7	NO	YES	YES	YES	NO
COMMON NAME :	XYLENE					
CAS NUMBER:	136-52-7	NO	YES	NO	YES	NO
COMMON NAME :	COBALT ALKANOATE					
CAS NUMBER:	95-63-6	NO	YES	NO	NO	NO
COMMON NAME :	PSEUDOCUMENE					
CAS NUMBER:	98-82-8	NO	YES	YES	YES	
COMMON NAME :	CUMENE					

AS OF THE DATE OF THIS MSDS, ALL OF THE COMPONENTS IN THIS PRODUCT ARE LISTED (OR ARE OTHERWISE EXEMPT FROM LISTING) ON THE TSCA INVENTORY. THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR (CONTROLLED PRODUCTS REGULATIONS) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

 -----  
 SECTION 16: OTHER INFORMATION  
 -----

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE AT THE TIME OF PREPARATION OF THIS DATA SHEET AND WHICH AKZO NOBEL PAINTS LLC BELIEVES TO BE RELIABLE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA. AKZO NOBEL PAINTS LLC SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS INFORMATION, OR OF ANY PRODUCT, METHOD OR APPARATUS MENTIONED AND YOU MUST MAKE YOUR OWN DETERMINATION OF ITS SUITABILITY AND COMPLETENESS FOR YOUR OWN USE, FOR THE PROTECTION OF THE ENVIRONMENT, AND THE HEALTH AND SAFETY OF YOUR EMPLOYEES AND USERS OF THIS MATERIAL.

-----  
SECTION 16: OTHER INFORMATION  
-----

COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD  
29CFR1910.1200.